



'CORRUPTION, A CRIME AGAINST NATION'

Vigilance and Anti-Corruption Bureau,
Directorate, Thiruvananthapuram –33.

E-mail: vig.vacb@kerala.gov.in

Phone No: 0471 2305393

No. 6771/2026-M1/DVACB

Dated: 28-10-2026

QUOTATION NOTICE

Quotation Number	M1-6771/2026-M1/DVACB
Due date and time for receipt of quotations	07.11.2026 02:00 PM
Date and time for opening of quotations	07.11.2026 03:00 PM
Date up to which the rates are to remain firm for acceptance	60 days from the date of acceptance of quotation
Designation and address of officer to whom the quotation is to be addressed	The Director, Vigilance & Anti Corruption Bureau, Law College Road, Vikas Bhavan (PO), Thiruvananthapuram
Superscription : Quotation No. M1-6771/2026-M1/DVACB for supply of Handy Cam/Camcorder	
Sealed quotations are invited from OEM/Vendors for the supply of the materials/services specified in the schedule attached below/overleaf from firms registered and operated in Kerala State. The rates quoted should be for providing of services at Vigilance and Anti Corruption Bureau Directorate. The necessary superscription, due date for the receipt of quotations, the date up to which the rates will have to remain firm for acceptance and the name and address of officer to whom the quotation is to be sent are noted above. Any quotation received after the time fixed on the due date is liable to be rejected. The maximum period required for providing of the service should also be mentioned.	

1. The acceptance of the quotations will be subject to the following conditions: Acceptance of the quotation constitutes a concluded contract.
2. Firms participating in the quotation must be registered and operational within the state of Kerala. The firm shall be responsible for providing required software support and personnel until integration is finalized.
3. The maximum period required for delivery of service should be mentioned.
4. Details of the requirements and conditions governing them can be obtained free of cost from Vigilance and Anti Corruption Bureau Directorate.
5. No representation for enhancement of price once accepted will be considered during the currency of the contract.
6. Any attempt on the part of tenderers or their agents to influence the Officers concerned in their favour by personal canvassing will disqualify the tenders.
7. The envelope containing the sealed quotation should be clearly labelled with 'Quotations' on the cover. Please ensure this marking is prominently displayed for identification.

Place : Thiruvananthapuram

Date : 28.10.2026

Items included in quotation No. M1-6771/2026-M1/DVACB dated
28/10/2026

SI No	Item Description	Recommended Specification
1	Handy Cam/Camcorder	'same as item description'

Digitally signed by
Ujjual Kumar G
Date: 28-10-2026
16:20:37

UJJUAL KUMAR G
SUPERINTENDENT OF
POLICE(INT)



< ZV-E10 II VLOG CAMERA

FULL SPECIFICATIONS AND FEATURES

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
COLOUR OPTIONS	☐	☐ ☐
General		
CAMERA TYPE	Interchangeable lens digital camera	Interchangeable lens digital camera
LENS MOUNT	E-mount	E-mount
Camera Section		
SENSOR TYPE	APS-C type (23.3 x 15.5 mm), Exmor R CMOS sensor	APS-C type (23.3 x 15.5 mm), Exmor R CMOS sensor
NUMBER OF PIXELS (TOTAL)	Approx. 27.0 megapixels	Approx. 27.0 megapixels
NUMBER OF PIXELS (EFFECTIVE)	Still images: Approx. 26.0 megapixels max. ¹² , Movies: Approx. 19.9 megapixels max. ¹²	Still images: Approx. 26.0 megapixels max. ¹² , Movies: Approx. 19.9 megapixels max. ¹²
OPTICAL LOW-PASS FILTER	-	-
COLOUR TEMPERATURE RANGE	2500 K–9900 K	2500 K–9900 K
ANTI-DUST SYSTEM	-	-

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
Recording (still images)		
RECORDING FORMAT	JPEG (DCF Ver. 2.0, Exif Ver. 2.3 2, MPF Baseline compliant), HEI F (MPEG-A MIAF compliant), RA W (Sony ARW 5.0 format compl iant)	JPEG (DCF Ver. 2.0, Exif Ver. 2.3 2, MPF Baseline compliant), HEI F (MPEG-A MIAF compliant), RA W (Sony ARW 5.0 format compl iant)
IMAGE SIZE (PIXELS) [3:2]	APS-C L: 6192 x 4128 (26 M), M: 4384 x 2920 (13 M), S: 3104 x 2 064 (6.4 M)	APS-C L: 6192 x 4128 (26 M), M: 4384 x 2920 (13 M), S: 3104 x 2 064 (6.4 M)
Recording (movie)		
VIDEO COMPRESSION	XAVC S: MPEG-4 AVC/H.264, X AVC HS: MPEG-H HEVC/H.265	XAVC S: MPEG-4 AVC/H.264, X AVC HS: MPEG-H HEVC/H.265
AUDIO RECORDING FORMAT	LPCM 2ch (48 kHz 16 bit), LPCM 2ch (48 kHz 24 bit) ¹³ , LPCM 4c h (48 kHz 24 bit) ¹³	LPCM 2ch (48 kHz 16 bit), LPCM 2ch (48 kHz 24 bit) ¹³ , LPCM 4c h (48 kHz 24 bit) ¹³
Recording System (movie)		
MOVIE RECORDING FORMAT (XAVC HS 4K)	3840 x 2160 (4:2:0, 10bit) (Appr ox.): 59.94p (150 Mbps/75 Mbp s/45 Mbps), 3840 x 2160 (4:2:0, 10bit) (Approx.): 50p (150 Mbp s/75 Mbps/45 Mbps), 3840 x 21 60 (4:2:0, 10bit) (Approx.): 23.9 8p (100 Mbps/50 Mbps/30 Mb ps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (200 Mbps/1 00 Mbps), 3840 x 2160 (4:2:2, 1 0bit) (Approx.): 50p (200 Mbp s/100 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (100 Mbps/50 Mbps)	3840 x 2160 (4:2:0, 10bit) (Appr ox.): 59.94p (150 Mbps/75 Mbp s/45 Mbps), 3840 x 2160 (4:2:0, 10bit) (Approx.): 50p (150 Mbp s/75 Mbps/45 Mbps), 3840 x 21 60 (4:2:0, 10bit) (Approx.): 23.9 8p (100 Mbps/50 Mbps/30 Mb ps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (200 Mbps/1 00 Mbps), 3840 x 2160 (4:2:2, 1 0bit) (Approx.): 50p (200 Mbp s/100 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (100 Mbps/50 Mbps)

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
MOVIE RECORDING FORMAT (XAVC S 4K)	3840 x 2160 (4:2:0, 8bit) (Approx.): 59.94p (150 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 50p (150 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 29.97p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 25p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 23.98p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (200 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 50p (200 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 29.97p (140 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 25p (140 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (100 Mbps)	3840 x 2160 (4:2:0, 8bit) (Approx.): 59.94p (150 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 50p (150 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 29.97p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 25p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:0, 8bit) (Approx.): 23.98p (100 Mbps/60 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (200 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 50p (200 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 29.97p (140 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 25p (140 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (100 Mbps)
MOVIE RECORDING FORMAT (XAVC S HD)	1920 x 1080 (4:2:0, 8bit) (Approx.): 119.88p (100 Mbps/60 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 100p (100 Mbps/60 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 59.94p (50 Mbps/25 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 50p (50 Mbps/25 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 29.97p (50 Mbps/16 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 25p (50 Mbps/16 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 23.98p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 59.94p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 50p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 29.97p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 25p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 23.98p (50 Mbps)	1920 x 1080 (4:2:0, 8bit) (Approx.): 119.88p (100 Mbps/60 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 100p (100 Mbps/60 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 59.94p (50 Mbps/25 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 50p (50 Mbps/25 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 29.97p (50 Mbps/16 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 25p (50 Mbps/16 Mbps), 1920 x 1080 (4:2:0, 8bit) (Approx.): 23.98p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 59.94p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 50p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 29.97p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 25p (50 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 23.98p (50 Mbps)

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
MOVIE RECORDING FORMAT (XAVC S-I 4K)	3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (600 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 50p (500 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 29.97p (300 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 25p (250 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (240 Mbps)	3840 x 2160 (4:2:2, 10bit) (Approx.): 59.94p (600 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 50p (500 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 29.97p (300 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 25p (250 Mbps), 3840 x 2160 (4:2:2, 10bit) (Approx.): 23.98p (240 Mbps)
MOVIE RECORDING FORMAT (XAVC S-I HD)	1920 x 1080 (4:2:2, 10bit) (Approx.): 59.94p (222 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 50p (185 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 29.97p (111 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 25p (93 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 23.98p (89 Mbps)	1920 x 1080 (4:2:2, 10bit) (Approx.): 59.94p (222 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 50p (185 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 29.97p (111 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 25p (93 Mbps), 1920 x 1080 (4:2:2, 10bit) (Approx.): 23.98p (89 Mbps)
Movie Functions		
SLOW AND QUICK MOTION (SHOOTING FRAME RATE)	Yes	Yes
PROXY RECORDING	Yes	Yes
TC/UB	Yes	Yes
RAW OUTPUT	-	-
MEMORY CARD SLOT	Slot for SD (UHS-I/II compliant) memory card	Slot for SD (UHS-I/II compliant) memory card
Focus System		
FOCUS TYPE	Fast Hybrid AF (phase-detection AF / contrast-detection AF)	Fast Hybrid AF (phase-detection AF / contrast-detection AF)

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
FOCUS POINT	Still images: Max. 759 points (phase-detection AF), Movies: Max. 495 points (phase-detection AF)	Still images: Max. 759 points (phase-detection AF), Movies: Max. 495 points (phase-detection AF)
FOCUS SENSITIVITY RANGE	EV-3 to EV20 (ISO100 equivalent with F2.0 lens attached)	EV-3 to EV20 (ISO100 equivalent with F2.0 lens attached)
RECOGNITION TARGET (STILL IMAGES)	Human, Animal, Bird	Human, Animal, Bird
RECOGNITION TARGET (MOVIES)	Human, Animal, Bird	Human, Animal, Bird
OTHER FEATURES	AF Level for Crossing. (Still), AF Track for Speed Changes. (Still), AF Subj. Shift Sensitivity (Movie), AF Transition Speed (Movie), Switch V/H AF Area, AF Area Regist., Circ. of Focus Point, Focus Map (Movie), AF Assist (Movie)	AF Level for Crossing. (Still), AF Track for Speed Changes. (Still), AF Subj. Shift Sensitivity (Movie), AF Transition Speed (Movie), Switch V/H AF Area, AF Area Regist., Circ. of Focus Point, Focus Map (Movie), AF Assist (Movie)
AF ILLUMINATOR	-	-
Exposure Control		
METERING TYPE	1200-zone evaluative metering	1200-zone evaluative metering
METERING SENSITIVITY	EV-3 to EV20 (ISO100 equivalent with F2.0 lens attached)	EV-3 to EV20 (ISO100 equivalent with F2.0 lens attached)
EXPOSURE COMPENSATION	+/- 5.0 EV (1/3 EV, 1/2 EV steps selectable)	+/- 5.0 EV (1/3 EV, 1/2 EV steps selectable)

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
ISO SENSITIVITY	Still images: ISO 100–32000 (expandable to ISO 50–102400), A UTO (ISO 100–6400, selectable lower limit and upper limit), Movies: ISO 100–32000 equivalent ¹⁴ , AUTO (ISO 100–6400, selectable lower limit and upper limit)	Still images: ISO 100–32000 (expandable to ISO 50–102400), A UTO (ISO 100–6400, selectable lower limit and upper limit), Movies: ISO 100–32000 equivalent ¹⁴ , AUTO (ISO 100–6400, selectable lower limit and upper limit)
ANTI-FLICKER SHOOT.	-	-
TYPE	-	-
LCD Screen		
MONITOR TYPE	7.5 cm (3.0-type) type TFT	7.5 cm (3.0-type) type TFT
TOUCH PANEL	Yes	Yes
NUMBER OF DOTS	1 036 800 dots	1 036 800 dots
ADJUSTABLE ANGLE	Opening Angle: Approx. 176 °, Rotation Angle: Approx. 270 °	Opening Angle: Approx. 176 °, Rotation Angle: Approx. 270 °
Other Features		
OTHER FEATURES	Product Showcase Set, Background Defocus, Soft Skin Effect, Creative Look, Custom function , Picture Profile, Time-lapse, Cinematic Vlog Setting, My Image Style, Vertical Display	Product Showcase Set, Background Defocus, Soft Skin Effect, Creative Look, Custom function , Picture Profile, Time-lapse, Cinematic Vlog Setting, My Image Style, Vertical Display
CLEAR IMAGE ZOOM (STILL IMAGES)	Approx. 2x	Approx. 2x
CLEAR IMAGE ZOOM (MOVIES)	Approx. 1.5x (4K), Approx. 2x (HD)	Approx. 1.5x (4K), Approx. 2x (HD)
Shutter		

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
SHUTTER TYPE	Electronic shutter	Electronic shutter
SHUTTER SPEED	Still images (Electronic shutter): 1/8000 to 30 s, Movies: 1/8000 to 1 s	Still images (Electronic shutter): 1/8000 to 30 s, Movies: 1/8000 to 1 s
FLASH SYNC. SPEED	1/30 s ¹⁵	1/30 s ¹⁵
Image stabilisation		
TYPE	Still images: Image stabilisation supported on lens, Movie: Image stabilisation supported on lens (Standard Mode)/Electronic (Active Mode)	Still images: Image stabilisation supported on lens, Movie: Image stabilisation supported on lens (Standard Mode)/Electronic (Active Mode)
COMPENSATION EFFECT	-	-
MODE	Still images: On/Off, Movie: Active/Standard/Off	Still images: On/Off, Movie: Active/Standard/Off
Flash		
TYPE	-	-
CONTROL	Pre-flash TTL	Pre-flash TTL
FLASH COMPENSATION	+/- 3.0 EV (switchable between 1/3 and 1/2 EV steps)	+/- 3.0 EV (switchable between 1/3 and 1/2 EV steps)
EXTERNAL FLASH COMPATIBILITY	Sony α System Flash compatible with Multi Interface Shoe, attach the shoe adaptor for flash compatibility with the Auto-lock accessory shoe	Sony α System Flash compatible with Multi Interface Shoe, attach the shoe adaptor for flash compatibility with the Auto-lock accessory shoe
Drive		

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
CONTINUOUS DRIVE SPEED (APPROX. MAX.)	Hi+: 11 fps ¹⁶	Hi+: 11 fps ¹⁶
NO. OF FRAME RECORDABLE (APPROX.)	JPEG Extra fine L: 143 frames ¹⁶ , JPEG Fine L: over 1000 frames ¹⁶ , JPEG Standard L: over 1000 frames ¹⁶ , RAW: 59 frames ¹⁶ , RAW and JPG: 44 frames ¹⁶ , RAW (Lossless Compressed): 22 frames ¹⁶ , RAW (Lossless Compressed) and JPEG: 17 frames ¹⁶	JPEG Extra fine L: 143 frames ¹⁶ , JPEG Fine L: over 1000 frames ¹⁶ , JPEG Standard L: over 1000 frames ¹⁶ , RAW: 59 frames ¹⁶ , RAW and JPG: 44 frames ¹⁶ , RAW (Lossless Compressed): 22 frames ¹⁶ , RAW (Lossless Compressed) and JPEG: 17 frames ¹⁶
PIXEL SHIFT MULTI SHOOTING	-	-
MODES	Enlarged display mode, Protect , Rating, Shot Mark (Movie), Divider Frame, Crop, Photo Capture	Enlarged display mode, Protect , Rating, Shot Mark (Movie), Divider Frame, Crop, Photo Capture
FUNCTIONS	Screen Reader, Focus Magnifier , Focus Map (Movie), Peaking Display, Subject Recognition in AF, Touch Focus, Touch Tracking, Touch Shutter, Touch AE, Vari-angle LCD screen, Custom function, Enlarge Menu Screen	Screen Reader, Focus Magnifier , Focus Map (Movie), Peaking Display, Subject Recognition in AF, Touch Focus, Touch Tracking, Touch Shutter, Touch AE, Vari-angle LCD screen, Custom function, Enlarge Menu Screen
Interface		
PC INTERFACE	Mass-storage / MTP	Mass-storage / MTP
USB TYPE-C TERMINAL	Yes (SuperSpeed USB 5 Gbps (USB 3.2) compatible)	Yes (SuperSpeed USB 5 Gbps (USB 3.2) compatible)
NFC	-	-
SYNC TERMINAL	-	-
WIRELESS LAN (BUILT-IN)	Yes (Wi-Fi Compatible, IEEE 802.11a/b/g/n/ac (2.4 GHz band/5 GHz band)) ¹⁷ ¹⁸	Yes (Wi-Fi Compatible, IEEE 802.11a/b/g/n/ac (2.4 GHz band/5 GHz band)) ¹⁷ ¹⁸

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
BLUETOOTH®	Yes (Bluetooth Standard Ver. 4.2 [2.4 GHz band])	Yes (Bluetooth Standard Ver. 4.2 [2.4 GHz band])
HDMI OUTPUT	HDMI micro connector (Type-D), 3840 x 2160 (59.94p / 50p / 29.97p / 25p / 23.98p) / 1920 x 1080 (59.94p / 50p / 23.98p) / 1920 x 1080 (59.94i / 50i), YCbCr 4:2:2 10bit / RGB 8 bit	HDMI micro connector (Type-D), 3840 x 2160 (59.94p / 50p / 29.97p / 25p / 23.98p) / 1920 x 1080 (59.94p / 50p / 23.98p) / 1920 x 1080 (59.94i / 50i), YCbCr 4:2:2 10bit / RGB 8 bit
MULTI INTERFACE SHOE	Yes (with Digital Audio Interface) ¹⁹	Yes (with Digital Audio Interface) ¹⁹
MIC TERMINAL	Yes (3.5 mm Stereo minijack)	Yes (3.5 mm Stereo minijack)
HEADPHONE TERMINAL	Yes (3.5 mm Stereo minijack)	Yes (3.5 mm Stereo minijack)
REMOTE CONTROL (WIRELESS)	Yes (Bluetooth remote control)	Yes (Bluetooth remote control)
LAN TERMINAL	-	-
FUNCTIONS	Send to smartphone, Remote control via smartphone, Remote Shooting	Send to smartphone, Remote control via smartphone, Remote Shooting
USB Streaming		
VIDEO DATA FORMAT	MJPEG, YUV420 ²⁰	MJPEG, YUV420 ²⁰
VIDEO RESOLUTION	3840 x 2160 (15p/30p), 3840 x 2160 (12.5p/25p), 1920 x 1080 (30p/60p), 1920 x 1080 (25p/50p), 1280 x 720 (30p), 1280 x 720 (25p)	3840 x 2160 (15p/30p), 3840 x 2160 (12.5p/25p), 1920 x 1080 (30p/60p), 1920 x 1080 (25p/50p), 1280 x 720 (30p), 1280 x 720 (25p)
AUDIO DATA FORMAT	LPCM 2ch (16 bit 48 kHz)	LPCM 2ch (16 bit 48 kHz)
Network streaming		

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
VIDEO DATA FORMAT	MPEG-4 AVC/H.264, MPEG-H H EVC/H.265 ²¹	MPEG-4 AVC/H.264, MPEG-H H EVC/H.265 ²¹
VIDEO RESOLUTION	3840 x 2160 (30p), 3840 x 2160 (25p), 2560 x 1440 (30p), 2560 x 1440 (25p), 1920 x 1080 (30p/60p), 1920 x 1080 (25p/50p), 1280 x 720 (30p/60p), 1280 x 720 (25p/50p)	3840 x 2160 (30p), 3840 x 2160 (25p), 2560 x 1440 (30p), 2560 x 1440 (25p), 1920 x 1080 (30p/60p), 1920 x 1080 (25p/50p), 1280 x 720 (30p/60p), 1280 x 720 (25p/50p)
AUDIO DATA FORMAT	AAC-LC 2ch (16bit 48 kHz)	AAC-LC 2ch (16bit 48 kHz)
PROTOCOL	RTMP, RTMPS, SRT	RTMP, RTMPS, SRT
Audio		
MICROPHONE	Built-in, stereo	Built-in, stereo
SPEAKER	Built-in, monaural	Built-in, monaural
SETTING	Shading, Chromatic Aberration, Distortion, Breathing (Movie)	Shading, Chromatic Aberration, Distortion, Breathing (Movie)
Power		
SUPPLIED BATTERY	One rechargeable battery pack NP-FZ100	One rechargeable battery pack NP-FZ100
BATTERY LIFE (STILL IMAGES)	Approx. 610 shots (LCD monitor) (CIPA standard) ²²	Approx. 610 shots (LCD monitor) (CIPA standard) ²²
BATTERY LIFE (MOVIE, ACTUAL RECORDING)	Approx. 130 min (LCD monitor) (CIPA standard) ²³	Approx. 130 min (LCD monitor) (CIPA standard) ²³
INTERNAL BATTERY CHARGE	Yes (Available with USB Type-C Terminal. USB Power Delivery compatible)	Yes (Available with USB Type-C Terminal. USB Power Delivery compatible)

2 Models	Body Only ZV-E10M2	Body + 16–50 mm 2 Power Zoom Lens (SELP16502) ZV-E10M2K
USB POWER SUPPLY	Yes (Available with USB Type-C Terminal. USB Power Delivery compatible)	Yes (Available with USB Type-C Terminal. USB Power Delivery compatible)
POWER CONSUMPTION WITH LCD SCREEN	Still images: Approx. 3.2 W (with E PZ 16–50 mm F3.5–5.6 OSS II lens attached), Movies: Approx. 5.0 W (with E PZ 16–50 mm F3.5–5.6 OSS II lens attached)	Still images: Approx. 3.2 W (with E PZ 16–50 mm F3.5–5.6 OSS II lens attached), Movies: Approx. 5.0 W (with E PZ 16–50 mm F3.5–5.6 OSS II lens attached)
Size and Weight		
BODY ONLY	Approx. 292 g/Approx. 10.3 oz	Approx. 292 g/Approx. 10.3 oz
DIMENSIONS (W X H X D)	Approx. 114.8 x 67.5 x 54.2 mm (from grip to monitor)/Approx. 4.63 x 2.75 x 2.25 inches (from grip to monitor)	Approx. 114.8 x 67.5 x 54.2 mm (from grip to monitor)/Approx. 4.63 x 2.75 x 2.25 inches (from grip to monitor)
OPERATING TEMPERATURE	32–104 °F / 0–40 °C	32–104 °F / 0–40 °C
Supplied Accessory		
WHAT'S IN THE BOX	Rechargeable Battery NP-FZ100, Shoulder strap, Wind Screen, Wind Screen Adaptor, Body cap	SELP16502, Rechargeable Battery NP-FZ100, Shoulder strap, Wind Screen, Wind Screen Adaptor, Lens cap